

R250H500

دستگاه جوش هیدرولیک ۲۵۰-۵۰۰

موارد استفاده: این دستگاه در خطوط انتقال آب و فاضلاب و نفت و گاز ویژه لوله های پلی اتیلن pe100 با pe63 - pe80 جوش سر به سر (Buttweld) مورد استفاده قرار میگیرد.

مشخصات: قابلیت جوش لوله های پلی اتیلن در سایزهای فشار کاری ۱۶ - ۱۰ - ۶ - ۴ - ۳/۲ - ۲/۵ - ۲ - ۲۵۰ - ۲۸۰ - ۳۱۵ - ۳۵۵ - ۴۰۰ - ۴۵۰ - ۵۰۰ میلیمتر و در

توضیحات: این دستگاه قابلیت جوشکاری در سایزهای ۲۰۰ - ۲۲۵ میلیمتر را دارد. ابعاد دستگاه (۱۱۵ * ۷۰ * ۷۰) با وزن ۱۷۵ کیلوگرم

متعلقات: ۱- باکس هیدرولیک (پاور پک) مجهز به شیر فرمان هیدرولیک، فشار سنج، شلنگهای هیدرولیک و کوپلینگ (ابعاد ۴۵ * ۵۰ * ۵۶) ۲- هیتر برقی ۳۰۰۰ وات با تفلون صنعتی و درجه تنظیم حرارت از ۵۰ تا ۳۰۰ درجه سانتیگراد (وزن هیتر ۳۰ کیلوگرم) ۳- رنده با گیربکس ۱ اسب سه فاز و تیغه فولادی

آبدیده از جنس spk و (وزن رنده ۶۸ کیلوگرم) ۴- غلتک (رویلر) جهت سهولت در هدایت لوله و تنظیم

لوله بر روی فکها. ۵- چرخ هدایت جهت سهولت در حمل و جابجایی دستگاه. ۶- فلنج گیر (چهار نظام) با قابلیت تنظیم در سایزهای مختلف

لوازم جانبی: لباس کار و دستکش، سی دی آموزشی جدول جوشکاری

Hydraulic welding-Machine H250-R500

Using cases: this machine is used in sewerage systems, especially in butt weld polyethylene-PE63,PE80,PE100

Qualifications: welding abilities of polyethylene pipes in 250-280-315-355-400-450-500 sizes in 2-2/5-3/2-4-6-10-16 atmospheric pressure

Machine dimensions: 70*70*115
Wight: 25kg **Accessories:** 1-power back hydraulic 2- Electric heater 3000 w 3-shaver 4- Regulative clamps 5- Roller, guiding wheel calibration certificate

